

# LIGHT DUTY PORTABLE LIFTS

330/660/770/1000/1100/1500/1650 LBS.

## CAPACITY

• 330/660/770/1000/1100/1500/1650 lbs.

## PLATFORM SIZES

• 24" wide x 36" long  
• 24" wide x 48" long

## BASE SIZES

• 17 1/2" wide x 36" long  
• 17 1/2" wide x 48" long

## TRAVEL

• 24" & 36"

## LOWERED HEIGHT

• 9 1/4"

ELF Lifts - see chart for above measurements

## SAFETY

• Velocity fuse on all cylinders  
• Upper limit by pass on ELF lifts

## POWER SUPPLIES

Foot Pump - manually powers lifts, foot release for controlled lowering.

Hand release on ELF lifts

## D/C Battery

Hand Held Pendant c/w built-in 12 volt 6 amp charger

## MAINTENANCE

• Hinged top for easy access to power unit and cylinders  
• Self lubricated bushings on all pivot points

## OPTIONS

• Oversized platforms  
• Rotating tops  
• Below safety skirting

## ELF 770 DOUBLE SCISSOR LIFT



## ELF 330/660/1100/1650



## ELF PORTABLE FOOT PUMP LIFTS MANUALLY POWERED SCISSOR LIFTS Economical Portable Lifts

MODEL NO.	CAPACITY (lbs.)	PLATFORM SIZE (W x L) (in.)	LOW HT (in.)	RAISED HT (in.)	HANDLE HT (in.)	WHEEL (DIAM.)	OVERALL SIZE (W x L) (in.)	STROKES TO MAX. HT
ELF330	330	17.75 X 27.5	8.75	29.5	38	4	17.75 X 36	26
ELF660	660	19.75 X 32	11	35.5	39	5	19.75 X 42	25
ELF770	770	19.75 X 32	11.25	51.5	39	5	19.75 X 42	52
ELF1100	1100	19.75 X 35.75	13.5	35.5	38	5	19.75 X 42	38
ELF1650	1650	20 X 39.25	16.5	40	39	6	20 X 53	52



## PORTABLE HAND PUMP LIFT

MODEL NO.	CAPACITY (LBS.)	STD. PLAT. BASE (W x L) (in.)	LOW HT (in.)	TRAVEL (in.)	TOTAL HT (in.)	STROKES TO MAX HT	WEIGHT (LBS)
PH24-6	660	19.675 X 32	10.62	24	34.5	1.5/stroke	200

## PORTABLE FOOT PUMP - MANUALLY POWERED SCISSOR LIFTS

MODEL NO.	CAPACITY (lbs.)	STD. PLAT. BASE (W x L) (in.)	OVERSIZED PLATFORMS (UP TO) (in.)	LOW HT (in.)	TRAVEL (in.)	TOTAL HT (in.)	OVERALL DIAM. (W x L x H) (in.)	STROKES TO MAX HT	SHIP WEIGHT (Lbs)
<b>24" TRAVEL</b>									
PF24-10	1,000	24 x 36	40 x 48	9 1/4	24	33	25 x 51 x 36	1"/stroke	265
PF24-15	1,500	24 x 36	40 x 48	9 1/4	24	33	25 x 51 x 36	1"/stroke	280
<b>36" TRAVEL</b>									
PF36-10	1,000	24 x 48	40 x 60	9 1/4	36	45	25 x 63 x 45	1"/stroke	295
PF36-15	1,500	24 x 48	40 x 60	9 1/4	36	45	25 x 63 x 45	1"/stroke	315



## PORTABLE D/C BATTERY POWER - HAND CONTROL SCISSOR LIFTS

MODEL NO.	CAPACITY (lbs.)	STD. PLAT. BASE (W x L) (in.)	OVERSIZED PLATFORMS (UP TO) (in.)	LOW HT (in.)	TRAVEL (in.)	TOTAL HT (in.)	OVERALL DIAM. (W x L x H) (in.)	SPEED TO MAX HT	SHIP WEIGHT (Lbs)
<b>24" TRAVEL</b>									
PB24-10	1,000	24 x 36	40 x 48	9 1/4	24	33	25 x 51 x 36	8 seconds	325
PB24-15	1,500	24 x 36	40 x 48	9 1/4	24	33	25 x 51 x 36	14 seconds	340
<b>36" TRAVEL</b>									
PB36-10	1,000	24 x 48	40 x 60	9 1/4	36	45	25 x 63 x 45	12 seconds	355
PB36-15	1,500	24 x 48	40 x 60	9 1/4	36	45	25 x 63 x 45	18 seconds	375



LIFT & TILTS