

TANDEM SCISSOR LIFT

1,000 / 2,000 / 4,000 / 6,000 / 8,000 / 10,000 / 12,000 LBS

LIFT & TILTS



CAPACITY

- 1,000/2,000/4,000/6,000/8,000/10,000/12,000 lbs.

PLATFORM SIZES

- 24" wide x 96" long to 48" wide x 240" long

TRAVEL

- 36", 48", 60"

LOWERED HEIGHT

- 9" & 12"

SAFETY

- Velocity fuse is standard on each cylinder
- Safety maintenance stop included with each lift

POWER SUPPLIES

- A/C 110/1/60 volt
Hand or foot operated
- A/C 460/575/3/60 volt
Hand or foot operated
- Air/Hydraulic
Foot operated
Hand operated available
- Internally mounted
- Easily accessible for maintenance or repair
- Motors - Single phase 1 h.p. and three phase 1-1/2 h.p. - hand or foot operated standard

OPTIONS



SPECIFICATIONS - STANDARD 24" WIDE BASE LIFT TABLES

MODEL NO.	CAPACITY (LBS.)	STD. PLAT. BASE (W x L) (IN.)	OVERSIZED PLATFORMS (UP TO) (IN.)	LOW HT (IN.)	RAISED HT (IN.)	UP SPEED (SEC.)	MOTOR (H.P.)	VOLT/PH/HZ	SHIP WEIGHT (LBS)
36" TRAVEL - 24" WIDE x 96" LONG PLATFORM/BASE									
TSL36-10	1,000	24 x 96	48 x 144	9	45	20	1	110/1/60	920
TSL36-20	2,000	24 x 96	48 x 144	9	45	30	1	110/1/60	950
TSL36-40	4,000	24 x 96	48 x 144	9	45	40	1	110/1/60	1050
TSL36-60	6,000	24 x 96	48 x 144	9	45	35	1	208, 220, 460, 575/3/60	1100
TSL36-80	8,000	24 x 96	48 x 144	9	45	45	1	208, 220, 460, 575/3/60	1500
TSL36-100	10,000	24 x 96	48 x 144	9	45	55	1	208, 220, 460, 575/3/60	1550
TSL36-120	12,000	24 x 96	48 x 144	9	45	57	1	208, 220, 460, 575/3/60	1600
48" TRAVEL - 24" WIDE x 144" LONG PLATFORM/BASE									
TSL48-10	1,000	24 x 144	48 x 192	9	57	32	1	110/1/60	1100
TSL48-20	2,000	24 x 144	48 x 192	9	57	43	1	110/1/60	1200
TSL48-40	4,000	24 x 144	48 x 192	9	57	55	1	110/1/60	1300
TSL48-60	6,000	24 x 144	48 x 192	9	57	45	1	208, 220, 460, 575/3/60	1350
TSL48-80	8,000	24 x 144	48 x 192	9	57	55	1	208, 220, 460, 575/3/60	1700
TSL48-100	10,000	24 x 144	48 x 192	9	57	60	1	208, 220, 460, 575/3/60	1750
TSL48-120	12,000	24 x 144	48 x 192	9	57	62	1	208, 220, 460, 575/3/60	1800
60" TRAVEL - 24" WIDE x 176" LONG PLATFORM/BASE									
TSL60-10	1,000	24 x 176	48 x 224	9	69	38	1	110/1/60	1650
TSL60-20	2,000	24 x 176	48 x 224	9	69	50	1	110/1/60	1700
TSL60-40	4,000	24 x 176	48 x 224	9	69	60	1	110/1/60	1770
TSL60-60	6,000	24 x 176	48 x 224	9	69	50	1	208, 220, 460, 575/3/60	2000
TSL60-80	8,000	24 x 176	48 x 224	9	69	65	1	208, 220, 460, 575/3/60	2400
TSL60-100	10,000	24 x 176	48 x 224	9	69	78	1	208, 220, 460, 575/3/60	2500
TSL60-120	12,000	24 x 176	48 x 224	9	69	80	1	208, 220, 460, 575/3/60	2600

MAINTENANCE

- Easy access to power unit and cylinders, maintenance bar provided
- Self lubricated bronze bushings on all wear points

OPTIONS

- Oversized platforms
- Beveled edges for pit mounting
- Eye-bolts for pit mounting
- Rotating tops (available)
 - spring detents
 - manual detents
- Roller conveyor, Ball transfer tops
- Bellow safety skirting
- Safety tape switch
- Safety touch bars
- Semi-portable
- Portable
- 42" high hand rails with toe boards
- Diamond plate platform, ramp & flip plates