

# LOADING DOCK

5,000 / 6,000 / 8,000 / 10,000 / 12,000 / 15,000 / 20,000 / 25,000 LBS

LIFT & TILTS



## SPECIFICATIONS - 72" PLATFORM WIDTH

MODEL NO.	CAPACITY (LBS.)	LOWERED HEIGHT (IN.)	VERTICAL TRAVEL (IN.)	BASE FRAME (IN.)	MOTOR (H.P.)	APPROX. LIFT TIME (SEC.)	APPROX. WEIGHT (LBS.)
<b>STANDARD PLATFORM SIZE 72" WIDE X 96" LONG</b>							
LD-5-7296	5,000	9	59	67 X 92	1	100	2,280
LD-6-7296	6,000	10	59	67 X 92	1	120	2,400
LD-8-7296	8,000	14	59	67 X 92	3	55	3,259
LD-10-7296	10,000	14	59	67 X 92	3	70	3,800
LD-12-7296	12,000	14	59	68 X 93	5	54	4,100
LD-15-7296	15,000	14	59	68 X 93	5	56	4,800
LD-20-7296	20,000	18	59	68 X 93	7.5	50	5,850
LD-25-7296	25,000	20	59	68 X 93	10	54	6,050
<b>STANDARD PLATFORM SIZE 72" WIDE X 120" LONG</b>							
LD-5-72120	5,000	9	59	67 X 92	1	100	2,500
LD-6-72120	6,000	10	59	67 X 92	1	120	2,600
LD-8-72120	8,000	14	59	67 X 92	3	55	3,400
LD-10-72120	10,000	14	59	67 X 92	3	70	4,500
LD-12-72120	12,000	14	59	68 X 114	5	54	6,200
LD-15-72120	15,000	14	59	68 X 114	5	56	6,800
LD-20-72120	20,000	18	59	68 X 114	7.5	50	8,000
LD-25-72120	25,000	20	59	68 X 114	10	54	8,200
<b>STANDARD PLATFORM SIZE 72" WIDE X 144" LONG</b>							
LD-12-72144	12,000	14	59	68 X 138	5	54	7,200
LD-15-72144	15,000	14	59	68 X 138	5	56	7,800
LD-20-72144	20,000	18	59	68 X 138	7.5	50	8,800
LD-25-72144	25,000	25	59	68 X 138	10	54	9,000

## SPECIFICATIONS - 96" PLATFORM WIDTH

MODEL NO.	CAPACITY (LBS.)	LOWERED HEIGHT (IN.)	VERTICAL TRAVEL (IN.)	BASE FRAME (IN.)	MOTOR (H.P.)	APPROX. LIFT TIME (SEC.)	APPROX. WEIGHT (LBS.)
<b>STANDARD PLATFORM SIZE 96" WIDE X 96" LONG</b>							
LD-5-9696	5,000	9	59	68 X 93	1	100	2,500
LD-6-9696	6,000	10	59	68 X 93	1	120	3,000
LD-8-9696	8,000	14	59	68 X 93	3	55	3,520
LD-10-9696	10,000	14	59	68 X 93	3	70	4,500
LD-12-9696	12,000	14	59	89 X 93	5	54	5,200
LD-15-9696	15,000	14	59	89 X 93	5	56	5,800
LD-20-9696	20,000	18	59	89 X 93	7.5	50	6,900
LD-25-9696	25,000	20	59	89 X 93	10	54	7,100
<b>STANDARD PLATFORM SIZE 96" WIDE X 120" LONG</b>							
LD-5-96120	5,000	9	59	68 X 93	1	100	2,800
LD-6-96120	6,000	10	59	68 X 93	1	120	3,400
LD-8-96120	8,000	14	59	68 X 93	3	55	3,900
LD-10-96120	10,000	14	59	68 X 93	3	70	4,200
LD-12-96120	12,000	14	59	89 X 114	5	54	6,900
LD-15-96120	15,000	14	59	89 X 114	5	56	7,500
LD-20-96120	20,000	18	59	89 X 114	7.5	50	8,500
LD-25-96120	25,000	20	59	89 X 114	10	54	8,700
<b>STANDARD PLATFORM SIZE 96" WIDE X 144" LONG</b>							
LD-12-96144	12,000	14	59	89 X 138	5	54	7,400
LD-15-96144	15,000	14	59	89 X 138	5	56	8,200
LD-20-96144	20,000	18	59	89 X 138	7.5	50	9,200
LD-25-96144	25,000	25	59	89 X 138	10	54	9,400

### CAPACITY

- 5,000 / 6,000 / 8,000 / 10,000 / 12,000 / 15,000 / 20,000 / 25,000 lbs.

### PLATFORM

- Checker plate
- Split plate  
18" high x 68" wide

### BASE SIZES

- Standard 67", 68, 89" wide x 92", 93", 114, 138" long

### TRAVEL

- 59"

### LOWERED HEIGHT OF LOADING DOCK

- Consult chart

### POWER SUPPLY

A/C 220/460/575 volt  
3 Phase (standard\*)

\* 5,000/6,000 lb. units use 1 H.P. single phase motors

- Three phase motors (hand operated controls standard)
- 10' Hose and cables
- Different HP available (ie. 5/7)

### OPTIONS

- Different platform sizes
- Bellow safety skirting / safety touch bars / beveled edge
- Limit switches / photo eyes
- Eye bolts - for moving lifts easily
- Semi-portable c/w dolly handle