

WINCH STACKERS with ADJUSTABLE FORKS



175/260/330/550/1,100/2,200 LBS



CAPACITY

• 175/260/330/550/1100/2200 lbs.

LIFT HEIGHT

• 41"/143"/159"/160"

LOWERED HEIGHT

• 2.8"/3.5"/3.6"/3.75"

SAFETY

• Brake on caster

OPTIONS

• Platforms for adjustable fork units

**WINCH STACKERS with ADJUSTABLE FORKS (AF)
MINI WINCH STACKER with ADJUSTABLE FORKS (AF)**

MODEL NO.	CAPACITY (lbs.)	LIFT HEIGHT (in.)	MIN. FORK HEIGHT (in.)	FORK WIDTH (in.)	INDIVIDUAL FORK WIDTH (in.)	FORK LENGTH (in.)	LOAD WHEEL	STEERING WHEEL	STRADDLE LEG HT. (in.)	WEIGHT (lbs.)
WS175AF	175	43	2.8	ADJ. 5-20	2	19.6	4" DIA. x 1.2" W	4" DIA. x 1.2" W	4	114
WS330AF	330	43	2.8	ADJ. 5-20	2	19.6	4" DIA. x 1.2" W	4" DIA. x 1.2" W	4	136
WS550AF	550	60	3.6	ADJ. 6-27	2.3	32	3" DIA. x 2" W	6" DIA. x 1.5" W	3.5	308
WS1100AF	1100	60	3.6	ADJ. 6-27	2.75	39	3" DIA. x 2" W	6" DIA. x 1.5" W	3.5	321
WS2200AF	2200	59	3.5	FIXED 21.25	6.3	45	3" DIA. x 3.7" W	6" DIA. x 2" W	3.25	400
LWS260AF	260	41	3.75	ADJ. 14-19	2	15.75	2" DIA. x .75" W	8" DIA. x 2" W	N/A	68

WINCH STACKERS with FIXED PLATFORM

- Manual winch and battery models available
- Available in adjustable fork and platform models
- Well designed light weight construction
- Very maneuverable
- Suitable for warehouses, retail, manufacturing, offices, any narrow applications, etc...

CAPACITY

• 175/220/330/440 lbs.

LIFT HEIGHT

• 59" / 67"

LOWERED HEIGHT

• 5.2"

SAFETY

• Brake on caster

OPTIONS

- Spindle attachment
 - Double spindle
 - Reel rotator
 - "V" cradle
- Other options available - please consult factory

175/220/330/440 LBS



MANUAL WINCH STACKERS with FIXED PLATFORM (FP)

MODEL NO.	CAPACITY (lbs.)	LIFT HEIGHT (in.)	MIN. PLAT. HEIGHT (in.)	PLATFORM (in.)	LOAD WHEEL	STEERING WHEEL	BATTERY	WEIGHT (lbs.)
WS220P	220	59	5.2	18.5 x 23.6	3" DIA	5" DIA.	N/A	105
WS440P	440	59	5.2	18.5 x 23.6	3" DIA	5" DIA.	N/A	154

ELECTRIC WINCH STACKER with FIXED PLATFORM (FP)

MODEL NO.	CAPACITY (lbs.)	LIFT HEIGHT (in.)	MIN. PLAT. HEIGHT (in.)	PLATFORM (in.)	LOAD WHEEL	STEERING WHEEL	BATTERY	WEIGHT (lbs.)
BWS175P	175	59	5.2	18.5 x 23.6	3" DIA	5" DIA.	24V, 7.2Ah	99
BWS220P	220	67	5.2	18.5 x 23.6	3" DIA	5" DIA.	24V, 7.2Ah	127
BWS330P	330	59	5.2	18.5 x 23.6	3" DIA	5" DIA.	24V, 7.2Ah	121