

FOOT PUMP STACKERS

440/880 LBS



CAPACITY

• 440/880 lbs.

LIFT HEIGHT

• 33"/47"/59"

LOWERED HEIGHT

• 3.2"/8"

SAFETY

• Brake on caster

POWER

• Simple and easy operation
- foot pump lift with hand valve for lowering

MAINTENANCE

• The cylinders have a hardened chromed ram with overload protection

OPTIONS

• Platforms for adjustable and fixed fork units

FOOT PUMP STACKERS with FIXED FORKS (FF)

MODEL NO.	CAPACITY (LBS.)	PUMPS TO MAX. LIFT	LIFT HEIGHT (IN.)	MIN. FORK HEIGHT (IN.)	O.A. FORK WIDTH (IN.)	O.A. FORK LENGTH (IN.)	LOAD WHEEL	STEERING WHEEL (IN.)	WEIGHT (LBS.)
FOOT PUMP STACKER with FIXED FORKS									
FS440FF33	440	15	33	3.2	20	24	3" DIA.	5	121
FS440FF47	440	23	47	3.2	20	24	3" DIA.	5	132
FS880FF33	880	30	33	3.2	21.6	25.6	3" DIA.	5	167
FS880FF47	880	45	47	3.2	21.6	25.6	3" DIA.	5	193
FS880FF59	880	58	59	3.2	21.6	25.6	3" DIA.	5	220

FOOT PUMP STACKERS with ADJUSTABLE FORKS (AF)

MODEL NO.	CAPACITY (LBS.)	PUMPS TO MAX. LIFT	LIFT HEIGHT (IN.)	MIN. FORK HEIGHT (IN.)	O.A. FORK WIDTH (IN.)	O.A. FORK LENGTH (IN.)	LOAD WHEEL	STEERING WHEEL (IN.)	WEIGHT (LBS.)
FOOT PUMP STACKER with ADJUSTABLE FORKS									
FS440AF33	440	15	33	3.2	ADJ. 5-20	24	3" DIA.	5	121
FS440AF47	440	23	47	3.2	ADJ. 5-20	24	3" DIA.	5	132
FS880AF33	880	30	33	3.2	ADJ. 5-21.6	25.6	3" DIA.	5	167
FS880AF47	880	45	47	3.2	ADJ. 5-21.6	25.6	3" DIA.	5	193
FS880AF59	880	58	59	3.2	ADJ. 5-21.6	25.6	3" DIA.	5	220

FOOT PUMP STACKERS with PLATFORM (P)

MODEL NO.	CAPACITY (LBS.)	PUMPS TO MAX. LIFT	LIFT HEIGHT (IN.)	MIN. PLATFORM HEIGHT (IN.)	O.A. PLATFORM WIDTH (IN.)	O.A. PLATFORM LENGTH (IN.)	LOAD WHEEL	STEERING WHEEL (IN.)	WEIGHT (LBS.)
FS440P33	440	15	33	8	20	24	5" DIA.	5	121
FS440P47	440	23	47	8	20	24	5" DIA.	5	132
FS880P33	880	30	33	8	21.6	25.6	6" DIA.	6	167
FS880P47	880	45	47	8	21.6	25.6	6" DIA.	6	193
FS880P59	880	58	59	8	21.6	25.6	6" DIA.	6	220