

ADJUSTABLE WORK STANDS

- Ideal for parts bins, moulds, dies, etc...
- Ergonomically positioned work reduces strain when work optimal height and angle
- Lightweight and mobile
- Complete with four swivel casters
- Angle of table adjusts from 0 - 40 degrees

CAPACITY

- 330 lbs.

HEIGHTS

- 20" to 28" / 28" to 42"

TILT ANGLE

- 0 - 40°

SAFETY

- Brake on casters



AWP



330 LBS

ADJUSTABLE WORK POSITIONERS (AWP)

MODEL NO.	CAPACITY (LBS.)	PLATFORM SIZE WxD (IN.)	TABLE HEIGHT RANGE (IN.)	TABLE ANGLE	CASTOR SIZE	WEIGHT (LBS.)
ADJUSTABLE WORK POSITIONERS						
AWP33-20	330	20" X 16"	20 TO 27	0 - 40°	3"	61
AWP33-28	330	20" X 16"	28 TO 42	0 - 40°	3"	66

LIFTS & TILTS

SCISSOR LIFT TABLES

2,200/4,400/8,800 LBS

- Ideal for loading and unloading of product
- Quality pump and cylinders

CAPACITY

- 2200 / 4400 / 8800 lbs.

PLATFORM SIZE

- 32.3" wide x 51.2" long
- 33.5" wide x 51.2" long (check specifications below)

LOW HEIGHT

- 8" / 9" / 9.5"

MAX. TABLE HEIGHT

- 39" / 41" / 43"

SAFETY

- Aluminum safety trip bar under complete perimeter of standard size lift table (safety trip bars are extra for larger platforms)
- 24v control voltage for hand held pendant
- Velocity fuse
- Removable lifting eyes to facilitate handling of lift table

POWER

- A/C 110v Power - 2,200, 4,400
- A/C 460/575 3 phase - 8,800

OPTIONS

- Safety skirting
- Larger platforms (safety trip bars are extra for larger platforms)
- Foot control



XL31-22



XL32-44



XL43-88

SCISSOR LIFT TABLES (XL)

MODEL NO.	CAPACITY (LBS.)	PLATFORM SIZE WxL (IN.)	BASE SIZE WxL (IN.)	MIN. TABLE HEIGHT (IN.)	MAX. TABLE HEIGHT (IN.)	TRAVEL (IN.)	LIFT SPEED (SECONDS)	WEIGHT (LBS.)
SCISSOR LIFT TABLES								
XL31-22	2200	32.3 x 51.2	25 X 49	8	39	31	20	352
XL32-44	4400	32.5 x 51.2	31 X 48	9	41	32	20	517
XL43-88	8800	47.3 x 67	35.4 X 63	9.5	43	33.5	40	825